



BP Bartran

Non zinc antiwear hydraulic oil

Description

The BP Bartran hydraulic oil range of premium lubricants are based on a carefully selected ashless additive system designed to meet and exceed the most exacting performance standards.

Application

The Bartran range is particularly suitable for hydraulic systems using vane and piston pumps where elevated operating temperatures are encountered. They are formulated for use in severely stressed systems in which high levels of antiwear performance and/or ultra fine filtration are required. They have been proven to be resistant to the effects of 'dieseling' in highly stressed systems such as plastic injection moulding and fatigue testing equipment where the application leads to rapid breakdown of more conventional products.

Bartran is suitable for a wide range of other applications requiring high levels of antiwear and superior oxidation performance.

Bartran range is fully compatible with the elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluropolymers.

Bartran is classified as follows:

DIN classification - HLP

ISO 6743/4 - Hydraulic Oils Type HM

Bartran grades meet the requirements of:

DIN 51524 Part 2

Cincinnati Milacron (P 68-69-70)

Denison HF-0 & HF-2

US Steel 126 & 127

Eaton (formally Vickers) I-286-S & M-2950-S

Bosch-Rexroth RE 07 075

Advantages

- Superior thermal and oxidative stability provides reliable performance and extended oil life in severe applications. Minimal deposit formation gives a cleaner system and reduced frequency of filter changes
- Superior antiwear performance provides excellent wear protection and long life and reduction in replacement part costs
- Outstanding filterability characteristics in both wet and dry conditions enables cost savings to be made due to increased filter life.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Versatile – can be used for other applications
- Good corrosion protection

Typical Characteristics

Test	Method	Units	5	10	15	22	32	46	68	100
Density @ 15°C	ISO 12185 / ASTM D4052	g/ml	0.83	0.86	0.87	0.87	0.87	0.88	0.88	0.88
K.V. @ 40°C	ISO 3104 / ASTM D445	mm ² /s	5	10	15	22	32	46	68	100
K.V. @ 100°C	ISO 3104 / ASTM D445	mm ² /s	-	2.7	3.2	4.25	5.26	6.65	8.6	11.1
Viscosity Index	ISO 2909 / ASTM 2270	-	-	90	-	>95	>95	>95	>95	>95
Pour Point	ISO 3016 / ASTM D97	°C	-30	-33	-27	-27	-27	-24	-21	-18
Flash Point, PMC	ISO 2719 / ASTM D93	°C	133	170	160	170	200	200	200	220
Foam Sequence I	ISO 6247 / ASTM D892	mls/mls	40/0	30/0	20/0	20/0	20/0	20/0	10/0	10/0
Demulsification @ 54°C	ISO 6614 / ASTM D1401	mins	3	5	10	10	15	15	15	15
Air Release @ 50°C	ISO / 9120 / ASTM D3427	mins	1	1	4	4	4	8	8	12
FZG (A8.3/90), fail stage	ISO 14635-1 / DIN 51354	-	-	-	-	-	12	12	12	12
Rust Test (24 hrs synthetic sea water)	ISO / 7210 / ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP, Bartran, and the BP logo are trademarks of BP p.l.c, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial
www.castrol.com/industrial