



## Product Data

### Vanellus C6 Global 15W-40

For reliability and protection

#### Description

BP Vanellus C6 Global is a 15W-40 heavy duty diesel engine oil designed to provide excellent engine protection in severe duty on and off road applications. BP Vanellus C6 Global 15W-40 is a versatile product which can be used in trucks, buses, LCVs, off-road vehicles and equipment and also in agricultural vehicles where API CH-4 performance is required.

#### Advantages

User benefits include:

- Excellent protection against wear and deposits provides peace of mind against breakdown and reduced maintenance costs
- Maintains engine cleanliness to deliver smooth running and reliable performance
- Stay in grade shear stability for controlled oil consumption and maintained oil pressure

#### Typical Characteristics

Name	Method	Units	Vanellus C6 Global 15W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.885
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	14.2
Viscosity, CCS -20C	ASTM D5293	mPa.s (cP)	< 7000
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	105
Viscosity Index	ASTM D2270	None	137
Ash, Sulphated	ASTM D874	% wt	1.3
Total Base Number, TBN	ASTM D2896	mg KOH/g	10
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	200

# Product Performance Claims

API CH-4

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Vanellus C6 Global 15W-40

27 Oct 2015

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW  
Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125  
[www.bp.com](http://www.bp.com)