



Product Data

BP Visco 3000 10W-30

CleanGuard Engine Protection Technology

Description

Cleaner engines last longer and run better.

BP Visco CleanGuard™ Engine Protection Technology keeps your engine cleaner and fights dirt - varnish, carbon and even deadly sludge in vital oilways.

BP Visco slows the formation of dirt at its source and wrap up dirt particles so that they cannot stick to sensitive engine parts.

Application

Visco 3000 10W-30 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SL or earlier specification 10W-30 lubricant.

Advantages

BP Visco 3000 10W-30 is a premium quality engine oil which provides:

- Keeps your engine cleaner*
- Advanced protection for normal driving conditions
- Reduced oil burnoff
- Superior anti-wear performance

* vs API SL requirements, piston cleanliness in ASTM Sequence III test limit

Typical Characteristics

Name	Method	Units	BP Visco 3000 10W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.8768
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.8
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6300
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	71
Viscosity Index	ASTM D2270	None	142
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	213

Product Performance Claims

API SL

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 3000 10W-30

19 Sep 2018

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125

www.bp.com