



Product Data

BP Visco 3000 5W-30

CleanGuard Engine Protection Technology

Description

Cleaner engines last longer and run better.

BP Visco with CleanGuard™ Engine Protection Technology keeps your engine cleaner* by helping to prevent deposit build up on sensitive engine parts.

*Based on Sequence IIH test, against API SP piston deposit limit

Application

BP Visco 3000 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an API SP or earlier specification 5W-30 lubricant.

Advantages

BP Visco 3000 is a high performance full synthetic engine oil with the following benefits:

- Improved engine cleanliness
- Advanced protection for normal driving conditions
- Reduced oil consumption
- Excellent anti-wear performance
- Outstanding performance in high temperatures

Typical Characteristics

Name	Method	Units	BP Visco 3000 5W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.850
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.5
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5700
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	65
Viscosity Index	ASTM D2270	None	151
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	223
Ash, Sulphated	ASTM D874	% wt	0.84

Product Performance Claims

API SP
ILSAC GF-6

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 3000 5W-30

10 Dec 2020

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125

www.bp.com