



Product Data

BP Visco 5000 10W-40

Cleanguard Engine Protection Technology

Description

BP Visco with CleanGuard™ Engine Protection Technology keeps your engine cleaner for longer.

Your car runs better if the engine is kept clean.

CleanGuard™ Technology keeps your engine clean by helping preventing dirt such as sludge from sticking to sensitive engine parts and the vital oil ways.

CleanGuard™ Technology also slows down the formation of sludge and wraps up dirt to prevent it sticking to the engine.

Application

BP Visco 5000 10W-40 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends API SN, ACEA A3/B4, A3/B3 or earlier specification 10W-40 lubricant.

BP Visco 5000 10W-40 is also approved for use in VW group vehicles that require a VW 501 01 / 505 00 specification 10W-40 and Mercedes-Benz vehicles that require a MB-Approval 229.1 10W-40 lubricant.

Advantages

BP Visco 5000 10W-40 is a premium part synthetic engine oil that provides:

- Improved engine cleanliness
- Advanced protection for normal driving conditions
- Reduced oil consumption

Typical Characteristics

Name	Method	Units	BP Visco 5000 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.872
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.7
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	6800
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	103
Viscosity Index	ASTM D2270	None	149
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	208
Ash, Sulphated	ASTM D874	% wt	1.2

Product Performance Claims

ACEA A3/B3, A3/B4
API SN
MB-Approval 229.1
VW 501 01 / 505 00
Meets Fiat 9.55535-D2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

BP Visco 5000 10W-40
25 Mar 2019
BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Lubricants UK Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW
Lubricants UK Telephone: 01793 512712, Automotive Technical Helpline: 0845 082 1719 Orders/Enquiries: 0845 6008125
www.bp.com