

TECHNICAL DATA SHEET

AIMOL Gear Oil GL-4 75W-90

Gear oil on synthetic basis for mechanical transmissions with special EP additives

APPLICATION

AIMOL Gear Oil GL-4 75W-90 is a gear oil on synthetic basis with additives for synchronised hand-changed gearboxes.

BENEFITS

AIMOL Gear Oil GL-4 75W-90 has the following properties:

- ◆ Good resistance against oxidation;
- ◆ Good rust prevention, anticorrosion and foam-inhibiting properties;
- ◆ A low pour point;
- ◆ Good extreme pressure (EP) properties.

PERFORMANCE LEVELS

AIMOL Gear Oil GL-4 75W-90 meets and exceeds the following performance levels/specifications:

- ◆ API-services GL-4
- ◆ MIL L-2105

TYPICAL FIGURES

SAE Grade	75W-90
Density at 15°C kg/m ³	0.885
Flashpoint C.O.C. in °C	206
Viscosity at 40°C in cSt	89.8
Viscosity at 100°C in cSt	15.4
Viscosity Index	182
Viscosity at -40°C in cP	<150000
Pour point in °C	-42

TECHNICAL DATA INFO LINE

Should you require additional information or advice on AIMOL products, please contact us as per the details below.

HEALTH AND SAFETY

AIMOL Gear Oil GL-4 75W-90 has no adverse health effects provided it is used as directed.

DISCLAIMER

Typical figures as indicated may vary per production cycle and can change at manufacturers' option. Specifications, however, are guaranteed. Because of continuous product research and development, the information within this data sheet is subject to change without any notification. Although every effort is made to ensure accurate information, A.I.M. bv accepts no liability for any loss or damage suffered caused by the incorrectness and/or incompleteness of this text, and as a result of using this product for any application other than explicitly stated in this data sheet.